

①PCRサイズ(10~13インチ) バイアス(旧サイズ)→ラジアル互換表

PCR												
インチ数	バイアス				ラジアル							
	サイズ	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅	80	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅	70	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅
10"	4.80-10	232	245	3 1/2	135/80R10	227	257	3 1/2				
					145/80R10	235	315	3 1/2-4				
	5.20-10	239	270	3 1/2	145/80R10	235	315	3 1/2-4				
12"	5.50-12	262	305	4	145/80R12	260	355	3 1/2-4	155/70R12	252	365	4 1/2-5
					155/80R12	266	400	4-4 1/2	165/70R12	262	412	4-5
	5.65-12	250	270	3 1/2-4	135/80R12	253	290	3 1/2-4	145/70R12	247	325	4-4 1/2
									155/70R12	252	365	4 1/2-5
	5.95-12	257	315	3 1/2-4	145/80R12	260	355	3 1/2-4	155/70R12	252	365	4 1/2-5
									165/70R12	262	412	4-5
	6.00-12	273	350	4-4 1/2	155/80R12	265	400	4-4 1/2	165/70R12	262	412	4-5
									175/70R12	265	450	5
13"	5.50-13	275	320	4-5	145/80R13	273	375	4-5	155/70R13	264	387	4 1/2-5
					155/80R13	279	425	4-5	165/70R13	274	437	4-5
	5.60-13	286	365	4-4 1/2	155/80R13	279	425	4-5	165/70R13	274	437	4-5
					165/80R13	286	475	4 1/2-5 1/2				
	6.15-13	275	375	4-5	155/80R13	279	425	4-5	165/70R13	274	437	4-5
									175/70R13	280	475	4 1/2-5 1/2
	6.45-13	286	430	4 1/2-5 1/2	165/80R13	286	475	4 1/2-5 1/2	175/70R13	280	475	4 1/2-5 1/2
					175/80R13	292	530	4 1/2-5 1/2	185/70R13	287	530	4 1/2-5 1/2
	6.50-13	295	450	4 1/2-5	175/80R13	292	530	4 1/2-5 1/2	185/70R13	287	530	4 1/2-5 1/2
					185/80R13	298	560	5-6	195/70R13	292	580	5 1/2
7.00-13	305	550	5	185/80R13	298	560	5-6	195/70R13	292	580	5 1/2	

②PCRサイズ(14~16インチ) バイアス(旧サイズ)→ラジアル互換表

PCR												
インチ数	バイアス				ラジアル							
	サイズ	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅	80	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅	70	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅
14"	6.15-14	288	395	4-5	155/80R14	292	450	4-5	175/70R14	293	500	4 1/2-6
	6.40-14	315	480	4 1/2-5	175/80R14	305	560	4 1/2-5 1/2	185/70R14	301	560	4 1/2-6
					185/80R14	312	600	5-6				
	6.45-14	299	455	4 1/2-5 1/2	165/80R14	298	500	4 1/2-5 1/2	175/70R14	293	500	4 1/2-6
					175/80R14	305	560	4 1/2-5 1/2	185/70R14	301	560	4 1/2-6
	6.95-14	306	490	4 1/2-5 1/2	175/80R14	305	560	4 1/2-5 1/2	185/70R14	301	560	4 1/2-6
					185/80R14	312	600	5-6	195/70R14	306	615	5-6 1/2
	7.00-14	317	520	5	185/80R14	312	600	5-6	195/70R14	306	615	5-6 1/2
					195/80R14	319	650	5-6	205/70R14	314	650	5-7
					175/80R15	316	600	4 1/2-6	195/70R15	316	630	5-6 1/2
									205/70R15	322	690	5-7
	7.35-14	313	540	5-6	185/80R14	312	600	5-6	195/70R14	306	615	5-6 1/2
					195/80R14	319	650	5-6	205/70R14	314	670	5-7
	7.50-14	325	665	5 1/2	205/80R14	326	710	5 1/2-6 1/2	205/70R14	314	670	5-7
7.75-14	321	590	5-6	195/80R14	319	650	5-6	195/70R14	306	615	5-6 1/2	
				205/80R14	326	710	5 1/2-6 1/2	205/70R14	314	670	5-7	
8.25-14	327	630	6	205/80R14	326	710	5 1/2-6 1/2	205/70R14	314	670	5-7	
15"	5.60-15	311	415	4 1/2	165/80R15	311	530	4 1/2-5				
					175/80R15	316	600	4 1/2-6				
	7.00-15	346	690	5	215/80R15	344	800	5 1/2-6 1/2	215/70R15	329	750	5 1/2-7
	7.10-15	344	660	5	195/80R15	331	670	5 1/2-6				
7.60-15	351	730	5 1/2	215/80R15	344	800	5 1/2-6 1/2	225/70R15	335	800	6-7 1/2	
16"	6.00-16	339	515	4	175/80R16	330	615	4 1/2-5 1/2				

③LTRサイズ(10~14インチ) バイアス(旧サイズ)→ラジアル互換表

LT														
インチ数	バイアス					ラジアル								
	サイズ	動的 負荷 半径 mm	負荷 能力 (最大) kg		適用 リム幅	95、90、85	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅	82	動的 負荷 半径 mm	負荷 能力 (最大) kg		適用 リム幅
10"	5.00-10	244	4PR	325/305	3.00-3.50	135/95R10	246	387/365	3 1/2-4	145R10	236	6PR	355/335	3-4
			6PR	370/350										
			8PR	430/410										
12"	4.50-12	258		415/395	3.00-3.50	135/95R12	271	450/425	3 1/2-4	145R12	261	8PR	520/495	3 1/2-4
	5.00-12	269		485/465	3.00-4.00	135/95R12	271	450/425	3 1/2-4	145R12	261	8PR	520/495	3 1/2-4
						145/95R12	280	500/475	4-4 1/2	155R12	266	8PR		
13"	5.00-13	281		535/510	4-4 1/2					145R13	274		550/525	3 1/2-4
										155R13	279		595/565	4-5
	5.50-13	293		610/580	4-5	155/95R13	301	670/630	4-4 1/2	165R13	287		670/640	4-5
										175R13	294		730/690	4 1/2-5 1/2
6.00-13	308		710/675	4-5	165/95R13	310	750/710	4 1/2-5	175R13	294		730/690	4 1/2-5 1/2	
14"	5.50-14	306		645/610	4-5					165R14	300		715/680	4-5
										175R14	307		775/735	4 1/2-5 1/2
	6.00-14	321		750/710	4-5	165/95R14	323	800/750	4 1/2-5	185R14	313		840/800	5-6
										195R14	321		935/890	5-6
	6.50-14	332		840/795	4 1/2-5	175/95R14	331	875/825	4 1/2-5 1/2	195R14	321		935/890	5-6
6.95-14	308		695	4 1/2-5 1/2						175R14	307		775/735	4 1/2-5 1/2
										185R14	313		840/800	5-6

⑤LTRサイズ(16インチ) バイアス(旧サイズ)→ラジアル互換表

LT																			
インチ数	バイアス					ラジアル													
	サイズ	動的 負荷 半径 mm	負荷 能力 (最大) kg		適用 リム幅	サイズ	動的 負荷 半径 mm	負荷 能力 (最大) kg		適用 リム幅	95、90、85	動的 負荷 半径 mm	負荷 能力 (最大) kg		適用 リム幅	80	動的 負荷 半径 mm	負荷能力 (最大)	
16"	6.50-16	356	6PR	785/745	4.50-5.50	6.50R16	361				205/85R16	365	1285/1215	5-6 1/2	195/80R17.5	366	8PR	925/900	5.25-6.00
			8PR	920/870					10PR	1060/1000									
			10PR	1010/960				5.50											
	7.00-16	367	6PR	880/840	5.00-5.50	7.00R16	372				215/85R16	373	1400/1320	5 1/2-7	205/80R17.5	373	8PR	1030/975	5.25-6.00
			8PR	1025/980				5.50	10PR	1150/1090									
			10PR	1130/1075					12PR	1250/1180									
	12PR	1230/1170		8PR	1090/1060	5.25-6.75													
	7.50-16	382	6PR	1010/960	5.50-6.00	7.50R16	386				225/85R16	380	1450/1360 ※14PRIはNG	6-7	225/80R17.5	388	14PR	1550/1500	6.00-6.75
			8PR	1175/1120				8PR	1175/1120	5.50-6.00									
			10PR	1330/1265				10PR	1330/1265										
			12PR	1440/1370	6.00			12PR	1440/1370	6.00									
			14PR	1510/1440				14PR	1510/1440										
	8.25-16	403	12PR	1575/1500	6.00-6.50	8.25R16	408	12PR	1575/1500	6.00-6.50	225/90R17.5	409	1750/1650	6-6.75					
	14PR	1710/1630	14PR	1710/1630															

⑥TBRサイズ バイアス(旧サイズ)→ラジアル互換表

TB												
インチ数	バイアス				ラジアル							
	サイズ	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅	サイズ	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅	サイズ	動的 負荷 半径 mm	負荷 能力 (最大) kg	適用 リム幅
18''	7.50-18	422	1750/1650	6.00-6.50	7.50R18	425	1750/1650	6.00-6.50	9R19.5	410	1900/1800	6.00-6.75
20''	7.50-20	447	1800/1700	6.00-6.50	7.50R20	447	1800/1700	6.00-6.50				
	8.25-20	467	2030/1930	6.00-7.00	8.25R20	469	2030/1930	6.50-7.00	9R22.5	469	2030/1930	6.00-6.75
	9.00-20	489	2415/2300	6.50-7.50	9.00R20	491	2415/2300	6.50-7.50	10R22.5	491	2415/2300	6.75-7.50
	10.00-20	505	2700/2425	7.00-8.00	10.00R20	507	2700/2425	7.00-8.00	11R22.5	507	2725/2500	7.50-8.25
	11.1-20	505	2750/2510	7.00-8.00	11.1R20	507	2750/2510	7.00-8.00	11R22.5	507	3000/2725	7.50-8.25
	11.00-20	519	3100/2785	7.50-8.50	11.00R20	522	3100/2785	7.50-8.50	12R22.5	522	3250/2900	8.25-9.00
	12.00-20	538	3250/3095	8.00-9.00	12.00R20	541	3250/3095	8.50-9.00				
					13/80R20	508	3650/3250	8.50-9.00				
24''	12.00-24	592	3660/3485	8.00-9.00	12.00R24	593	3660/3485	8.50-9.00				