

産業車両用空気入りタイヤ（ニューマチックタイヤ） 空気圧表

タイヤサイズ	PR	パターン	適用リム	対応空気圧 (kPa)
4.00-8	4	LUG	3.00D DT	500
	6	PL LUG PS		725
5.00-8	8	PL PL-SB LUG ES PS SE	3.00D TB 3.50D DT 3.00D DT	800
	10	PL PL-SB	3.00D TB 3.00D DT ^(?)	1000
		ES		900
	PS	700		
500-9	8	LUG	3.50D DT 3.00D DT	800
6.00-9	10	PL PL-SB LUG ES PS SE	4.00E TB 4.00E DT	850
	12	PL	4.00E TB	1000
6.50-10	10	PL PL-SB LUG ES PS SE	5.00F TB 5.00F DT	775
	12	PL PL-SB ES PS		900
4.50-12	6	PL LUG	3.00D DT 3.00D DC	675
	8	LUG PS PL	3.50D DT 3.50D DC	900
7.00-12	12	PL PL-SB LUG ES PS SE	5.00S TB 5.00S DT	850
	14	PL	5.00S TB	1000
8.25-12	12	LUG	5.00S DT	750
5.50-15	8	PL PL-SB LUG PS SE	4.50E DT 4.50E SDC	725
6.00-15	10	PL PL-SB LUG PS	4.50E DT 4.50E SDC	825
7.50-15	12	PL	6.00S IR 6.50T IR	775
	12	PL LUG PS	6.50T IR	700
	14	PL PL-SB LUG PS		800
	16	PL		900
	18	PI	1000	
7.50-16	8	LUG PS	6.00GS SDC	525
	10	PL LUG		650
	12	PL PL-SB LUG PS		6.00GS DT 6.00GS SDC ^(†)
9.00-16	10	PG	7.00N DT 7.00N SDC	550
	14	LUG PS		750
15×4½-8	8	PLM	3.25I DT 3.00D TB 3.00D DT	700
	12	PLM ES	3.00D TB	1000
16×6-8	10	PLM ES	4.33R TB 4.25DT	850
18×7-8	10	PLN-B ES PS PLF	4.33R TB 4.25DT	750
	14	PLN-B PLN-B.SB ES PS		900
	16	PLN-B ES PS PLF	4.33R TB	1000
21×8-9	10	PLM PLM-SB ES PS	6.00E TB 6.00E DT	625
	14	PLM PLM-SB ES PS PLF	900	
23×9-10	16	PLF ES PS PLM	6.50F TB 6.50F DT	900
27×10-12	12	PL	8.00G TB 8.00G DT	650
28×8-15	12	PL PL-SB PS	6.50T IR 6.00S IR	775
28×9-15	12	PL PL-SB PS ES	7.00T IR	700
	14	PL ES PS		800
250-15	16	PS PL	7.50V IR 7.5	850
	18	PL	7.00T IR 7.0	900
300-15	18	PL PL-SB PS	8.00V IR 8.0	800
7.00-15MS	12	PL PL-SB PS	6.00S (IRに限る)	700
8.25-20	12	TKMmk II	6.50T 6.00S 7.00T	700
	14	PGM PS		825
9.00-20	14	TKMmk II PGM	7.00T 7.50V	750
10.00-20	14	TKMmk II	7.50V 7.00T 8.00V	700
	16			800
11.00-20	16	TKMmk II SE	8.00V 7.50V 8.50V	775
12.00-20	18	TKMmk II EV188	8.50V 9.00V	800
13.00-24	18	EV188	9.00V 8.50V	750
14.00-24	24	EV188	10.00VI	900
16.00-25	28	EV188	11.25/2.0	900
	32			1000
8.25R15	18	ML CM	6.50T	1000
28×8R-15	-	EL AMD	6.50T IR 6.00S	1000
28×9R-15	-	EL ML	7.00T IR	1000

備考	下線のあるリムが標準リム、その他は許容リムを示す。	
注	(†)	空気圧700kPa (7.00kgf/cm ²) 以下の場合に適用する。
	(?)	空気圧900kPa (9.00kgf/cm ²) 以下の場合に適用する。